

SG3000AK/OP, SG3010AK/OP, SG3100AK, SG3200AK,
SG3210AK/OP & SG3300AK

Sounders & Sounder/Beacons

VANDERBILT



Key Features include:

- Multi-function warning device for various applications
- Easy to install & commission
- Selectable operating voltage
- Screw terminals
- Robust construction for external applications
- Internal components have environmental protection
- Low current consumption
- Tamper protected

SG3000AK/OP, SG3010AK/OP, SG3100AK, SG3200AK, SG3210AK/OP & SG3300AK

Sounders & Sounder/Beacons

VANDERBILT

■ Technical data

	SG3000AK/OP	SG3010AK/OP	SG3100AK	SG3200AK/OP	SG3200AK/OP	SG3300AK
Type	Sounder/Beacon	Sounder/Beacon	Sounder	Sounder/Beacon	Sounder/Beacon	Sounder
Dimensions (W x H x D) mm	205 x 258 x 88	205 x 258 x 88	205 x 200	205 x 193 x 88	205 x 193 x 88	205 x 135
Beacon current	200mA	200mA	-	200mA	200mA	-
Flash frequency	1.2Hz	1.2Hz	-	1.2Hz	1.2Hz	-
Beacon						
- Colour	Red	Red	-	Red	Red	-
- Material	Polycarbonate	Polycarbonate	-	Polycarbonate	Polycarbonate	-
VdS Approval	G199005	G199005	G199006	G199005	G199005	G199006
Housing						
- Material	Stainless Steel/Aluminium 1.5mm					
- Colour	RAL 9002					
Environmental						
- Class	Class IV VdS					
- Operating	-25 ... +60°C					
Input voltage	12V DC +/- 15% or 24V DC +/- 10%					
Sounder						
- Output	>100dB at1m					
- Current	350Ma at 12V DC					
Tamper	Micro switch for lid removal					

■ Ordering Information

Type	Art.-No.	Description	Weight
SG3000AK/OP	NDE6:9908400013	SG3000AK/OP Compact alerting	1.70Kg
SG3010AK/OP	NDE6:9908410013	SG3010AK/OP Compact alerting	0.XXKg
SG3100AK	NDE6:9908420013	SG3100AK Acoustic signal transmitter	1.70Kg
SG3200AK/OP	NDE6:9908440013	SG3200AK/OP Compact alerting	1.50Kg
SG3300AK	NDE6:9908460013	SG3300AK Acoustic signal transmitter	1.50Kg