

HMD-LWA-AES/CDA2

Mifare Reader

VANDERBILT



Key Features include:

- Compact proximity reader
- Robust construction
- Suitable for internal and external applications
- VdS approved
- Compatible with the SPC system via SPCA210
- Wiegand interface

HMD-LWA-AES/CDA2

Mifare Reader

VANDERBILT

■ Technical data

System compatibility	SPC via CPCA210 interface
Interface to Controller	Wiegand
Supply voltage	12/24VDC
Current Consumption	26/40 mA
Tamper Switch	No
Card/Fob compatibility	Mifare Classic, Classic 4K, Ultralight, Ultralight C, light, mini & DESFire EV1
External Indications	Red, green & yellow LED
Cable	Factory fitted 4m of 10 core cable
Keypad	No
Operating temperature	-15°C to +65°C
Application	Internal or external
IP Rating	IP65
Construction	
– Front plate	Black ABS plastic
– Enclosure	Anodised aluminium
Environmental	Class IV
Dimensions (W x H x D)	50 x 80 x 25 mm
Approvals	VdS G115050

■ Accessories

Type	Art.-No.	Description	Weight
HMD-TS2-SW-S	N54547-Z101-A600	HMD-TS2-SW-S Mifare DESFire key fob	0.004Kg

■ Ordering Information

Type	Art.-No.	Description	Weight
HMD-LWA-AES/CDA2	N54547-Z101-A300	HMD-LWA-AES/CDA2 Mifare read Wiegand	0.360Kg