

# HMD-TKSV-SES-S/CDA2

Mifare Keypad Reader

VANDERBILT



## Key Features include:

- Compact proximity reader complete with keypad
- Robust construction
- Suitable for internal and external applications
- VdS approved
- Compatible with the SPC system via SPCA210
- Wiegand interface

# HMD-TKSV-SES-S/CDA2

## Mifare Keypad Reader

VANDERBILT

### ■ Technical Data

System compatibility	SPC via CPCA210 interface
Interface to Controller	Wiegand
Supply Voltage	12/24VDC
Current Consumption	65/120 mA
Tamper Switch	No
Card/Fob compatibility	Mifare Classic 1K, Classic 4K, Ultralight, Ultralight C, light, Mini, DESFire EV1 & ISO14443-A
External Indications	Red, green & yellow LED
Cable	Factory fitted 4m of 10 core cable
Keypad	0 to 9, * & #
Operating temperature	-15°C to +65°C
Application	Internal and external
IP rating	IP64
Construction	
– Front plate	Black ABS plastic
– Enclosure	Anodised aluminium
Environmental	Class IV
Dimensions (W x H x D)	99 x 99x 20 mm
Approvals	VdS G115051

### ■ Accessories

Type	Art.-No.	Description	Weight
HMD-TS2-SW-S	N54547-Z101-A500	HMD-TS2-SW-S Mifare DESFire key fob	0.004Kg

### ■ Ordering Information

Type	Art.-No.	Description	Weight
HMD-TKSV-SES-S/CDA2	N54547-Z101-A400	HMD-TKSV-SES-S/CDA2 Mifare keypad reader security Wiegand	0.54Kg