

Codelock

Access Control

VANDERBILT



- **One lock with two codes**
- **Sturdy construction for outdoor and indoor use**
- **Best selling codelock in the world**

The V42 is the best-selling codelock in the world. It is compact and easy to use with a modern design that is suitable for either indoor or outdoor mounting. The V42 has a capacity of two four-digit codes. One can be used by residents while the other is used by the property care taker, for example. All settings are made directly in the unit.



Technical Data

V42

Operating voltage	12 to 24 VAC/DC
Current consumption	8 mA in standby
Inputs	Exit button requests with delay. Two separate for code disable.
Outputs	Voltage-free relay contact, max. 1 A, 28 VDC.
Opening time	1–30 sec.
Door capacity	1
Code capacity	Two four-digit codes
Operating temperature	-35 to +55 °C
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH2 or SH1 rain cover.
IP rating	IP54
Housing	Cast metal with stainless steel buttons and security lock
Colour	Grey
Dimensions (W x H x D)	80 x 140 x 40 mm

Details for ordering

Type	Part no	Designation	Weight
V42	V24246-C3552-A1	Codelock with two codes	0.72 kg

The information in this document contains general descriptions of technical options available, which do not always have to be present in individual cases. The required features should therefore be specified in each individual case at the time of closing the contract.

© Vanderbilt International (IRL) Ltd. • Document no. A-100190-1 • Edition: 2015-06-15 • Document version: 1.0

Vanderbilt International (IRL) Ltd.
Clonshaugh Business and Technology Park
Clonshaugh
Dublin 17
Ireland

www.vanderbiltindustries.com